


IRK.350 SERIES High Voltage Diode/Diode

FEATURES

- ❖ *High voltage.*
- ❖ *Electrically isolated base plate.*
- ❖ *3000 V_{RMS} isolating voltage.*
- ❖ *Industrial standard package.*
- ❖ *Simplified mechanical designs, rapid assembly.*
- ❖ *High surge capability.*
- ❖ *Large creepage distances.*
- ❖ *Aluminum Nitride*



DESCRIPTION

This IRK series of Power Modules uses power diodes in three basic configurations. The semiconductors are electrically isolated from the metal base, allowing common heatsinks and compact assemblies to be built. They can be interconnected to form single phase or three phase bridges. These modules are intended for general purpose applications such as battery chargers, welders and plating equipment.

MAJOR RATINGS & CHARACTERISTICS

Parameters	IRK.350	Units
$I_{F(AV)}$ @ $T_c = 100^\circ\text{C}$	350	A
$I_{F(RMS)}$	502	A
I_{FSM} @ 50 Hz	10110	A
I^2t @ 50 Hz	511	kA ² s
$I^2\sqrt{t}$	5110	kA ² $\sqrt{s}$
V_{RRM} range	400 to 1600	V
T_j	-40 to 135	$^\circ\text{C}$

POWER MODULES

IRK .350 SERIES

ELECTRICAL SPECIFICATION VOLTAGE RATINGS

Type Number	Voltage Code	V_{RRM} , max. repetitive peak reverse and off-state voltage blocking voltage V	V_{RSM} , max. non-repetitive peak reverse voltage V	I_{RRM} max. @ 150°C mA
IRK.350	04	400	500	50
	06	600	700	50
	08	800	900	50
	10	1000	1100	50
	12	1200	1300	50
	14	1400	1500	50
	16	1600	1700	50

FORWARD CONDUCTION

	Parameters	IRK.350)	Units	Conditions	
$I_{F(AV)}$	Max. average forward current	350	A	180°C conduction, half sine wave	
	@ case temperature	100	°C		
$I_{F(RMS)}$	Max. RMS forward current	502	A	as AC switch	
I_{FSM}	Max. peak, one cycle forward non-repetitive surge current	10110	A	t = 10ms	Sinusoidal half wave, Initial $T_J = T_J$ max.
I^2t	Maximum I^2t for fusing	511	kA ² s	t = 10ms	Sinusoidal half wave, Initial $T_J = T_J$ max.
$I^2\sqrt{t}$	Maximum $I^2\sqrt{t}$ for fusing	5110	kA ² √s	t = 0.1 to 10ms. No voltage reapplied.	
$V_{F(TO)}$	Threshold voltage	0.69	V	$T_J = T_J$ max.	
r_t	Forward slope resistance	0.59	mΩ	$T_J = T_J$ max.	
V_{FM}	Max. forward voltage drop	1.25	V	$I_{FM} = \pi \times I_{F(AV)}$, $T_J = T_J$ max., 180° conduction AV. power = $V_{F(TO)} \times I_{F(AV)} + r_t \times (I_{F(RMS)})^2$	

POWER MODULES

IRK.350 SERIES


THERMAL AND MECHANICAL SPECIFICATIONS

	Parameters	IRK.350	Units	Conditions	
T _J	Junction operating temperature	-40 to 135	°C		
T _{stg}	Storage temperature range	-40 to 150	°C		
R _{thj-c}	Max. internal thermal resistance, junction to case	0.125	K/W	IRKD../IRKJ../IRKC..	Per junction, DC operation
R _{thC-S}	Thermal resistance, case to heatsink	0.035	K/W	Mounting surface flat, smooth and greased	
T	Mounting torque ±10% Module to heatsink	4 to 6	Nm	A mounting compound is recommended and the torque should be rechecked after a period of about 3 hours to allow for the spread of the compound.	
	Busbar to module	8 to 10	Nm		
Wt	Approximate weight	600	g		

BLOCKING

	Parameter	IRK.350	Units	Conditions
I_{RRM}	Max. peak reverse leakage current	50	mA	$T_J = 150^\circ\text{C}$
V_{INS}	RMS isolation voltage	3000	V	50 Hz, circuit to base, all terminals shorted, $t=1\text{sec}$




OUTLINE DIAGRAM



POWER MODULES

IRK .350 Series

Circuit Configuration Table

IRKD 	IRKC 	IRKJ 
--	--	--

Ordering Information Table

IRK	D	350	/	16
①	②	③		④
① - Module type ② - Circuit configuration (See Circuit Configuration table) ③ - Current Code ④ - Voltage Code (See Voltage Ratings table)				

POWER MODULES

IRK .350 Series




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 4 - Forward Power Loss Characteristics

POWER MODULES

IRK .350 Series




Fig. 5 -ForwardPowerLossCharacteristics




Fig. 6 -ForwardPowerLossCharacteristics




Fig. 7 - Forward Power Loss Characteristics

POWER MODULES

IRK .350 Series




Fig. 8 -MaximumNon-Repetitive Surge Current




Fig. 9 -MaximumNon-Repetitive Surge Current




Fig. 10-Forward Voltage Drop Characteristics




Fig. 11 - Thermal Impedance Z_{thJC} Characteristics

Last Update : Feb. 2008